

according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier EXAMPLE Dangerous mixture

Substance / mixture mixture

UFI P300-A06R-300M-GH76

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Degreasing agent.

Main intended use

PC-CLN-2 All-purpose (or multi-purpose) non-abrasive cleaners including degreasing

agents (unless otherwise specified in other subcategories of cleaning products)

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Name or trade name Trial ltd.

Address Trial 123, Trial Test 8, 180 00

Czech Republic

Identification number (CRN)12345678VAT Reg NoCZ12345678Phone+420 725 582 495E-mailsupport@sblcore.comWeb addresswww.sblcore.com

Competent person responsible for the safety data sheet

Name Trial ltd.

1.4. Emergency telephone number

National Health Service (NHS) 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 2, H225

Asp. Tox. 1, H304

Skin Irrit. 2, H315

Skin Sens. 1, H317

Eye Irrit. 2, H319

STOT SE 3, H336

STOT RE 2, H373 (hearing organs, kidneys)

Aquatic Chronic 2, H411

Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to hearing organs, the kidneys through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

ethylbenzene cyclohexane

fenoxaprop-P-ethyl (ISO)

isopropanol

Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

H373 May cause damage to hearing organs, the kidneys through prolonged or

repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 Registration number: 01-2119489370-35	ethylbenzene	20	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs)	1
Index: 601-017-00-1 CAS: 110-82-7 EC: 203-806-2 Registration number: 01-2119463273-41	cyclohexane	10-<15	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	1, 2
Index: 607-707-00-9 CAS: 71283-80-2 Registration number: 01-3179417542-24	fenoxaprop-P-ethyl (ISO)	10	Skin Sens. 1, H317 STOT RE 2, H373 (kidneys) Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25	isopropanol	9	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	1
Index: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 Registration number: 01-2119457610-43	ethanol	5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2, H319: C ≥ 50 %	1

Notes

- 1 A substance for which exposure limits are set.
- 2 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Provide medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause drowsiness or dizziness.

If on skin

May cause an allergic skin reaction.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture						
Creation date	05th December 2024	Revision no.				
Revision date		Version	1.0			

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water. Do not allow to enter drains.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Contaminated work clothing should not be allowed out of the workplace. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Content	Packaging type	Material of package
435 ml	can / tin	ALU
2,5 l	can / tin	ALU

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

United Kingdom

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

	p.:	accexpectate attack	(· · · · · · · · · · · · · · · · · · ·
Substance name (component)		Туре	Value
cyclohexane (CAS: 110-82-7)		WEL 8h	350 mg/m ³





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

United Kingdom

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Substance name (component)	Туре	Value
	WEL 8h	100 ppm
cyclohexane (CAS: 110-82-7)	WEL 15min	1050 mg/m ³
	WEL 15min	300 ppm
	WEL 8h	999 mg/m ³
iconrepond (CAS: 67, 62, 0)	WEL 8h	400 ppm
isopropanol (CAS: 67–63–0)	WEL 15min	1250 mg/m ³
	WEL 15min	500 ppm
othonol (CAS: 64-17-E)	WEL 8h	1920 mg/m ³
ethanol (CAS: 64–17–5)	WEL 8h	1000 ppm

United Kingdom

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Substance name (component)	Туре	Value
	WEL 8h	441 mg/m ³
ethylbenzene (CAS: 100–41–4)	WEL 8h	100 ppm
ethytberizerie (CAS: 100-41-4)	WEL 15min	552 mg/m ³
	WEL 15min	125 ppm

Notes

Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Mask with a filter against organic vapours in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE	Dangerous	mixture
----------------	------------------	---------

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

Appearance

physical state liquid at 20 °C

form liquid color colourless color intensity transparent data not available

pH 7-8 (undiluted at 20 °C) ethanol (CAS: 64-17-5) 7 (>80% solution at 20 °C)

Melting point/freezing point data not available

Initial boiling point and boiling range 120 °C ethanol (CAS: 64-17-5) -114 °C

Flash point 18 °C ethanol (CAS: 64-17-5) >17 °C

Flammability (solid, gas) data not available

Upper/lower flammability or explosive limits

explosive limits data not available
Vapour pressure data not available
isopropanol (CAS: 67-63-0) 43 hPa at 20 °C

Solubility(ies)

solubility in water data not available

cyclohexane (CAS: 110-82-7) <0.1 g/l Partition coefficient: n-octanol/water 3.1

Auto-ignition temperature data not available

cyclohexane (CAS: 110-82-7) 260 °C

Decomposition temperature data not available

Viscosity

Kinematic viscosity data not available

Density 0.934 g/cm³

cyclohexane (CAS: 110-82-7) 0.78 g/cm³

isopropanol (CAS: 67-63-0) 0.79 g/cm³

9.2. Other information

not available

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixtur	е
---------------------------------	---

Revision date Version 1.0

05th December 2024

10.4. Conditions to avoid

Creation date

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

Revision no.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

cyclohexane						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Dermal	LD ₅₀		>2000 mg/kg		Rat	
Oral	LD ₅₀		>5000 mg/kg bw/day		Rat	F/M

ethanol						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Inhalation (vapor)	LC ₅₀		124.7 mg/l	4 hours	Rat	
Inhalation (vapor)	LC ₅₀		116.9 mg/l	4 hours	Rat	
Inhalation (vapor)	LC ₅₀		133.8 mg/l	4 hours	Rat	

ethylbenzene						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀		3500 mg/kg		Rat	
Dermal	LD ₅₀		17800 mg/kg		Rat	
Dermal	LD ₅₀		15433 mg/kg		Rabbit	
Inhalation (vapor)	LC ₅₀		17.4 mg/l	4 hours	Rat	
Oral	LD ₅₀		4769 mg/kg		Rat	
Inhalation (vapor)	LC ₅₀		17400 mg/kg	4 hours	Rat	





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

isopropanol						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Inhalation (vapor)	LC ₅₀	OECD 403	>10000 ppm	6 hours	Rat	F/M

Skin corrosion/irritation

Causes skin irritation.

ethylbenzene								
Route of exposure	Result	Exposure time	Species					
	Slightly irritating		Rabbit					

Serious eye damage/irritation

Causes serious eye irritation.

cyclohexane									
Route of exposure	Result	Method	Exposure time	Species					
	Slightly irritating			Rabbit					
ethanol									
Route of exposure	Result	Method	Exposure time	Species					
	Irritating			Rabbit					
ethylbenzene									
Route of exposure	Result	Method	Exposure time	Species					
	Irritating			Rabbit					
isopropanol									
Route of exposure	Result	Method	Exposure time	Species					
Eye	Serious eye damage	OECD 405		Rabbit					

Respiratory or skin sensitisation

May cause an allergic skin reaction.

cyclohexane										
Route of exposure	Result	Exposure time	Species	Sex						
	Not sensitizing									
ethylbenzene										
Route of exposure	Result	Exposure time	Species	Sex						
	Not sensitizing		Human							





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

isopropanol										
Route of exposure Result Exposure time Species Sex										
	Not sensitizing		Guinea-pig	F/M						

Germ cell mutagenicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

sopropanol									
Result	Exposure time	Specific target organ	Species	Sex					
Negative without metabolic activation, Negative with metabolic activation		Ovary	Guinea-pig	F/M					

Carcinogenicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanol										
Route of exposure	Parameter	Value	Result	Species	Sex					
Oral			Indeterminate	Rat						

Reproductive toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanol										
Effect	Parameter	Value	Result	Species	Sex					
Effects on fertility	NOAEL	>16000 ppm	No effect	Rat						
	NOAEL	5200 mg/kg/24h	Indeterminate	Rat						

ethylbenzene											
Effect	Parameter	Value	Result	Species	Sex						
	NOAEL	4.3 mg/l	Indeterminate	Rat							

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

ethanol										
Route of exposure	Parameter	Value	Exposure time	Specific target organ	Result	Species	Sex			
Inhalation	LOAEL	2.6 mg/l	30 minutes	Nervous system	Drowsiness, Dizziness	Human				





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

ethanol									
Route of exposure	Parameter	Value	Exposure time	Specific target organ	Result	Species	Sex		
Inhalation	LOAEL	9.4 mg/l		Lungs	Indeterminat e	Human			

ethylbenzene	ethylbenzene											
Route of exposure	Parameter	Value	Exposure time	Specific target organ	Result	Species	Sex					
Inhalation	NOAEL			Nervous system	Drowsiness, Dizziness	Human						

Toxicity for specific target organ - repeated exposure

May cause damage to hearing organs, the kidneys through prolonged or repeated exposure.

cyclohexane											
Route of exposure	Parameter	Value	Exposure time	Specific target organ	Result	Species	Sex				
Inhalation	NOAEC	500 mg/l				Mouse					
Inhalation	NOAEC	2000 ppm				Mouse					

ethylbenzen	е						
Route of exposure	Parameter	Value	Exposure time	Specific target organ	Result	Species	Sex
Inhalation	NOAEL	1.1 mg/l		Kidney	Indeterminat e	Rat	
Inhalation	NOAEL	1.1 mg/l	103 weeks	Liver	Indeterminat e	Mouse	
Inhalation	NOAEL	3.4 mg/l	28 days	Bone marrow	Indeterminat e	Rat	
Inhalation	NOAEL	2.4 mg/l	5 days		Indeterminat e	Rat	
Inhalation	NOAEL	3.3 mg/l	103 weeks	Endocrine system	Indeterminat e	Mouse	

isopropanol								
Route of exposure	Parameter	Value	Exposure time	Specific target organ	Result	Species	Sex	
Inhalation (vapor)	NOEC	500 ppm				Rat (Rattus norvegicus)	F/M	

Aspiration hazard

May be fatal if swallowed and enters airways. Data for the components of the mixture are not available.





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Acute toxicity

cyclohexane	cyclohexane						
Parameter	Value	Exposure time	Species	Environmen t	Value determination		
EC ₅₀	3.78 mg/l	48 hours	Daphnia (Daphnia magna)				
EC ₅₀	3.4 mg/l	72 hours	Algae				
IC ₅₀	0.9 mg/l	72 hours	Algae				
LC ₅₀	9.317 mg/l	96 hours	Fish (Oncorhynchus mykiss)				

ethanol					
Parameter	Value	Exposure time	Species	Environmen t	Value determination
EC ₀	3.9 g/l	200 hours	Fish		Experimentally
EC ₅₀	>10000 mg/l	48 hours	Daphnia		Experimentally
IC ₅₀	8800 mg/l	96 hours	Algae		Experimentally

ethylbenzene						
Parameter	Value	Exposure time	Species	Environmen t	Value determination	
EC ₅₀	1.81 mg/l	48 hours	Daphnia		Experimentally	
IC ₅₀	3.6 mg/l	72 hours	Algae		Experimentally	
LC ₅₀	4.2 mg/l	96 hours	Fish		Experimentally	

isopropanol					
Parameter	Value	Exposure time	Species	Environmen t	Value determination
EC ₅₀	>10000 mg/l	48 hours	Daphnia (Daphnia magna)		
LC ₅₀	9640 mg/l	96 hours	Fish	Fresh water	

Chronic toxicity

cyclohexane					
Parameter	Value	Exposure time	Species	Environmen t	Value determination
NOEC	0.94 mg/l	72 hours	Algae		

ethanol					
Parameter Value	Value	Exposure time	Species	Environmen	Value
	value	Exposure time	Species	t	determination
LC ₅₀	9248 mg/l	48 hours	Invertebrates		Experimentally





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

ethanol					
Parameter	Value	Exposure time	Species	Environmen t	Value determination
NOEC	250 mg/l	120 hours	Fish (Oncorhynchus mykiss)		Experimentally
NOEC	1000 mg/l	120 hours	Fish		Experimentally

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Other adverse effects

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Producer Responsibility Obligations (Packaging Waste) Regulations 2007 (S.I. No. 871 of 2007). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

14 06 03* other solvents and solvent mixtures

Packaging waste type code

15 01 02 plastic packaging

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (ethylbenzene)





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

I

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant

Additional information

Hazard identification No. 33
UN number 1993

Classification code

Safety signs 3+hazardous for the environment



Tunnel restriction code (D/E)

Air transport - ICAO/IATA

Packaging instructions passenger 351 Cargo packaging instructions 361

Marine transport - IMDG

EmS (emergency plan) F-E, S-E MFAG 310

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Clean Air Act 1993 as amended. The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Public health act 1961. Environmental Protection Act 1990 as amended. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).





according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous r	nixture
----------------------------	---------

Creation date 05th December 2024 Revision no.

Revision date 1.0 Version

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

cyclohexane

Restriction	Conditions of restriction
57	1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of neoprene-based contact adhesives in concentrations equal to or greater than 0,1 % by weight in package sizes greater than 350 g.
	2. Neoprene-based contact adhesives containing cyclohexane and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010.
	3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that neoprene-based contact
	adhesives containing cyclohexane in concentrations equal to or greater than 0,1 % by weight that are placed on the market for supply to the general public after 27 December 2010 are visibly, legibly and indelibly marked as follows:
	"— This product is not to be used under conditions of poor ventilation.— This product is not to be used for carpet laying.".

15.2. Chemical safety assessment

not available

HOOE

SECTION 16: Other information

A list of standard	l riek nhraege	used in the	safety data shee	+
A list of standard	. 115K DIII 85 6 5	useu III IIIe	Salety data silet	;L

H225	Highly flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H336	May cause drowsiness or dizziness.	
H373	May cause damage to hearing organs, the kidneys through prolonged or repeated exposure.	
H373	May cause damage to hearing organs through prolonged or repeated exposure.	
H373	May cause damage to the kidneys through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
Guidelines for safe handling used in the safety data sheet		

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.

Wear protective gloves.

IF SWALLOWED: Immediately call a doctor. P301+P310

P331 Do NOT induce vomiting.

P391 Collect spillage.

Store in a well-ventilated place. Keep cool. P403+P235



P280



according to Regulation (EC) No 1907/2006 (REACH) as amended

EXAMPLE Dangerous mixture

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox. Acute toxicity

ADR European agreement concerning the international carriage of dangerous goods

by road

Aquatic Acute Hazardous to the aquatic environment

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Asp. Tox. Aspiration hazard

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

EC Identification code for each substance listed in EINECS

EC₀ Concentration of a substance when it is affected 0 % of the population EC₅₀ Concentration of a substance when it is affected 50 % of the population EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EU European Union

EuPCS European Product Categorisation System

Eye Irrit. Eye irritation Flam. Liq. Flammable liquid

IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

IC50Concentration causing 50% blockadeICAOInternational Civil Aviation OrganizationIMDGInternational Maritime Dangerous Goods

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

 LC_{50} Lethal concentration of a substance in which it can be expected death of 50%

of the population

 $\ensuremath{\text{LD}_{50}}$ Lethal dose of a substance in which it can be expected death of 50% of the

population

LOAEL Lowest observed adverse effect level log Kow Octanol-water partition coefficient

MARPOL International Convention for the Prevention of Pollution from Ships

NOAEC No observed adverse effect concentration

NOAELNo observed adverse effect levelNOECNo observed effect concentrationOELOccupational Exposure Limits

PBT Persistent, bioaccumulative and toxic

PMT Persistent, mobile and toxic

ppm Parts per million





according to Regulation (EC) No 1907/2006 (REACH) as amended

Creation date 05th December 2024 Revision no.

Revision date Version 1.0

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

Skin Irrit. Skin irritation
Skin Sens. Skin sensitization

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very persistent and very bioaccumulative

vPvM Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

